



1



2



3



4



5



6



7



8

**1 Pressure Wash:** A thorough, high-pressure, hot water wash deep-cleans the surface and cracks for a better bond between the existing surface and the crack repair and court surfacing products.

**2 Crack Filling:** Cracks are cleaned and filled with court patch binder. Foam material is used in larger cracks when necessary.

**3 Binder Preparation:** Court patch binder is scraped and sanded to produce a smooth surface.

**4 Micro Sealant Tape:** Riteway™ micro-sealant tape is the first step of the patented Riteway™ Crack Repair System. This tape allows the crack to expand and contract while the tape stays intact, flexing with the crack.

**5 Fabric Installation:** Riteway™ Crack Repair System fabric installation is the second

step of the Riteway™ system. This fabric is installed over the micro-sealant tape, creating a bridged mesh system over the crack. The repair then receives multiple coats of acrylic resurfacer to blend the repair with the existing court. The edges are machine sanded to create a seamless repair.

**6 Resurfacer overlay:** Heavy-bodied acrylic resurfacer coating is applied to the entire surface. Acrylic resurfacer not only covers and levels any repairs and surface imperfections, it contains angular aggregate creating a rough texture. This texture creates a desired surface pace while providing an excellent bonding surface for the acrylic color surfacing material.

**7 Play area color surfacing:** Court area dimensions are located and the corners of the playing court are marked. Two coats of

acrylic color surfacing material fortified with 80-mesh rounded sand is applied to the playing court area. The end result is a durable surface with proper ball bounce and pace.

**8 Boundary area color surfacing:** Court boundaries are reestablished with a chalk snap line. Two coats of acrylic color surfacing material fortified with 80-mesh rounded sand is applied the boundary areas.

**9 Completed Court Renovation:** (top) Playing lines are masked using a specialized tape machine and masonry line. Each line is then applied using line paint specifically manufactured for tennis courts. The final result is a new, professionally-applied ready-for-play surface on existing courts.

*The staff at Nagle Athletic Surfaces, Inc. has served Central and Western New York and Pennsylvania for more than 20 years. We have been an active member of the American Sports Builders Association since 1994.*

**CALL TODAY to schedule a FREE athletic facility evaluation.**



1-800-388-5713  
www.nagleathletic.com  
email: info@nagleathletic.com

